

**1 Identification**

- Product identifier
- Trade name: Epifanes Easy-Flow
- Relevant identified uses of the substance or mixture and uses advised against
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC10 Roller application or brushing
- Environmental release category  
ERC10b Wide dispersive outdoor use of long-life articles and materials with high or intended release (including abrasive processing)  
ERC2 Formulation of preparations
- Application of the substance / the mixture  
See our technical datasheet for application of this product.
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:  
W.Heeren & Zoon bv.  
P.O. box 166  
1430 AD Aalsmeer  
Netherlands  
tel.+31-(0)297-360366  
fax +31-(0)297-342078  
email: r&d@epifanes.nl
- Information department: environment protection department
- Emergency telephone number:  
Emergency Phone Number (24 hours) CHEMTREC (800-424-9300)  
Outside US: 703-527-3887

**2 Hazard(s) identification**

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- Classification according to Directive 67/548/EEC or Directive 1999/45/EC  
R10-66: Flammable. Repeated exposure may cause skin dryness or cracking.
- Information concerning particular hazards for human and environment:  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.  
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
- Classification system:  
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.
- Label elements
- GHS label elements  
The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Trade name: Epifanes Easy-Flow

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Naphtha (petroleum), hydrotreated heavy (Note-p)

· Hazard statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0  
Fire = 2  
Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0  
Fire = 2  
Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

**3 Composition/information on ingredients**

· Chemical characterization: Mixtures

· Description:

Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 64742-48-9 EINECS: 265-150-3 Reg.nr.: 01-2119463258-33	Naphtha (petroleum), hydrotreated heavy (Note-p) ☒ Xn R65 R10-66 ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304	25-50%
---	---	--------

(Contd. on page 3)

Trade name: Epifanes Easy-Flow

(Contd. of page 2)

· Additional information:

Note P: The substance does not have to be classified as a carcinogen or mutagen as can be shown that the substance contains less than 0.1% (w / w) benzene (EINECS No 200-753-7.). This note applies only to certain complex oil-derived substances in Part 3.

For the wording of the listed risk phrases refer to section 16.

\* **4 First-aid measures**

- Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed  
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

\* **5 Fire-fighting measures**

- Extinguishing media
- Suitable extinguishing agents:  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture  
No further relevant information available.
- Advice for firefighters
- Protective equipment: No special measures required.

\* **6 Accidental release measures**

- Personal precautions, protective equipment and emergency procedures  
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:  
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

\* **7 Handling and storage**

- Handling:
- Precautions for safe handling  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

(Contd. on page 4)

Trade name: Epifanes Easy-Flow

(Contd. of page 3)

- Information about protection against explosions and fires:  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- Conditions for safe storage, including any incompatibilities
- Storage:  
Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- Additional information about design of technical systems:  
No further data; see item 7.
- Control parameters
- Components with limit values that require monitoring at the workplace:  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- ~~Additional information:~~  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.  
The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.
- Breathing equipment:  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.  
Filter AX
- Protection of hands:



### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Trade name: Epifanes Easy-Flow

(Contd. of page 4)

- For the permanent contact gloves made of the following materials are suitable:  
nitrile rubber;  
recommended glove thickness > 0.45mm. permeability / permeation time: > 480 min.  
according to EN 374.
- As protection from splashes gloves made of the following materials are suitable:  
chloroprene; glove thickness > 0.7mm, breakthrough time > 60min. according to EN 374.  
nitrile rubber; glove thickness > 0.3 mm, breakthrough time > 60min. volgens EN 374.
- Eye protection:



Tightly sealed goggles

**9 Physical and chemical properties**

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Fluid
Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	150 °C (302 °F)
· Flash point:	45 °C (113 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	0.87049 g/cm <sup>3</sup> (7.264 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.

(Contd. on page 6)

Trade name: Epifanes Easy-Flow

(Contd. of page 5)

· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	15 s (DIN 53211/4)
· Solvent content:	
Organic solvents:	39.6 %
VOC content:	39.6 %
	VOC content: 344.6 g/l / 2.88 lb/gl
Solids content:	60.4 %
· Other information	No further relevant information available.

**10 Stability and reactivity**

- Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided:  
No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

**11 Toxicological information**

- Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy (Note-p)

Oral	LD50	>5000 mg/kg bw (rat)
Dermal	LD50	>5000 mg/kg bw (rabbit) ((24h))
Inhalative	LC50	>5000 mg/m <sup>3</sup> (vapour) (rat) ((8h))

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

- Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7	xylene	3
136-52-7	cobalt bis(2-ethylhexanoate)	2B

- NTP (National Toxicology Program)
- None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)
- None of the ingredients is listed.

Trade name: Epifanes Easy-Flow

(Contd. of page 6)

**12 Ecological information**

· Toxicity

· Aquatic toxicity:

64742-48-9 Naphtha (petroleum), hydrotreated heavy (Note-p)

EL50 (48h)	>1000 mg/l ((Daphnia magna-OECD 202))
EbL50 (72h)	>1000 mg/l (Pseudokirchneriella subcapitata-OECD 201)
ErL (72h)	>1000 mg/l (Pseudokirchneriella subcapitata-OECD 201)
LL50 (96h)	>1000 mg/l ((Onorhynchus mykiss OECD 203))
NOELR (72h)	3 mg/l ((Pseudo. subcapitata-biomass-OECD 201))
	100 mg/l ((Pseudo. subcap. growth rate OECD 201))

- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

**13 Disposal considerations**

- Waste treatment methods
- Recommendation:  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

**14 Transport information**

- UN-Number
- DOT, ADR, IMDG, IATA UN1263
- UN proper shipping name
- DOT CONSUMER COMMODITY, ORM-D  
Paint
- ADR 1263 Paint
- IMDG CONSUMER COMMODITY, ORM-D  
PAINT
- IATA PAINT

(Contd. on page 8)

Trade name: Epifanes Easy-Flow

(Contd. of page 7)

· Transport hazard class(es)

· DOT



· Class 3 Flammable liquids  
· Label 3

· ADR, IMDG, IATA



· Class 3 Flammable liquids  
· Label 3

· Packing group

· DOT, ADR, IMDG, IATA III

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user

Warning: Flammable liquids

· Danger code (Kemler):

30

· EMS Number:

F-E, S-E

· Transport in bulk according to Annex

II of MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

· Quantity limitations

On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

· Remarks:

CERCLA/DOT RQ: 617gal./4786 lbs.

· ADR

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging:

30 ml

Maximum net quantity per outer packaging:

1000 ml

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging:

30 ml

Maximum net quantity per outer packaging:

1000 ml

· UN "Model Regulation":

UN1263, Paint, 3, III



Trade name: Epifanes Easy-Flow

(Contd. of page 8)

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

136-52-7 cobalt bis(2-ethylhexanoate)

· TSCA (Toxic Substances Control Act):

64742-48-9 Naphtha (petroleum), hydrotreated heavy (Note-p)

8016-13-5 Extracts and fysical modified derivats in fishoil. It contain mostly the glycerids of C14-18- en C16-22- unsaturated fatty acids. (mixed fish).

8001-26-1 Linseed oil

1330-20-7 xylene

68409-80-3 Isomers of fatty acid calcium salts, C6-C19

22464-99-9 Zirconiumoctoate, 12 % Zr

136-52-7 cobalt bis(2-ethylhexanoate)

112-34-5 2-(2-butoxyethoxy)ethanol

98-55-5 p-menth-1-en-8-ol

8006-64-2 Turpentine, oil

8000-41-7 Terpeenolie, terpene oil

125-12-2 exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-ylacetate

2500-83-6 Verdyl acetaat, Verdyl acetate, 3a,4,5,6,7,7a-hexahydro-4,7-methanoiden-5(6)-yl acetaat

8000-48-4 Eucalyptus olie (- globulus), Eucalypyus oil (-globulus)

138-86-3 dipentene

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

1330-20-7 xylene

I

· TLV (Threshold Limit Value established by ACGIH)

1330-20-7 xylene

A4

· MAK (German Maximum Workplace Concentration)

8006-64-2 Turpentine, oil

3A

(Contd. on page 10)

Trade name: Epifanes Easy-Flow

(Contd. of page 9)

- NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- GHS label elements  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



GHS02



GHS08

- Signal word Danger
- Hazard-determining components of labeling:  
Naphtha (petroleum), hydrotreated heavy (Note-p)
- Hazard statements  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.
- Precautionary statements  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- National regulations:
- Technical instructions (air):

Class	Share in %
NK	25-50

- Water hazard class:  
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- Chemical safety assessment:  
A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Date of preparation / last revision 03/31/2015 / 2
- Abbreviations and acronyms:  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association

(Contd. on page 11)

Trade name: Epifanes Easy-Flow

(Contd. of page 10)

ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
Flam. Liq. 3: Flammable liquids, Hazard Category 3  
Asp. Tox. 1: Aspiration hazard, Hazard Category 1  
\* Data compared to the previous version altered.