

**1 Identification**

- Product identifier
- Trade name: Epifanes Epoxy Finishing Filler (comp.A)
- Relevant identified uses of the substance or mixture and uses advised against
- Product category  
PC9b Fillers, putties, plasters, modelling clay  
PC9a Coatings and paints, thinners, paint removers
- Process category  
PROC5 Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)  
PROC10 Roller application or brushing
- Environmental release category ERC2 Formulation of preparations
- Application of the substance / the mixture  
See our technical datasheet for application of this product.
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:  
W.Heeren & Zoon bv.  
P.O. box 166  
1430 AD Aalsmeer  
Netherlands  
tel.+31-(0)297-360366  
fax +31-(0)297-342078  
email: r&d@epifanes.nl
- Information department: environment protection department
- Emergency telephone number:  
Emergency Phone Number (24 hours) CHEMTREC (800-424-9300)  
Outside US: 703-527-3887

**2 Hazard(s) identification**

- Classification of the substance or mixture



GHS08 Health hazard

Carc. 2                    H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2    H315 Causes skin irritation.

Eye Irrit. 2A    H319 Causes serious eye irritation.

Skin Sens. 1    H317 May cause an allergic skin reaction.

- Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R36/38-43:            Irritating to eyes and skin. May cause sensitisation by skin contact.



N; Dangerous for the environment

R51/53:                Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- Information concerning particular hazards for human and environment:  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)

Trade name: Epifanes Epoxy Finishing Filler (comp.A)

(Contd. of page 1)

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07 GHS08

· Signal word Warning

· Hazard-determining components of labeling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>)

reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700)

1,6-hexanediol diglycidyl ether

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1  
Fire = 1  
Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1  
Fire = 1  
Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.








Trade name: Epifanes Epoxy Finishing Filler (comp.A)

(Contd. of page 2)

### 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description:  
Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)  	10-25%
CAS: 9003-36-5 NLP: 500-033-5 Reg.nr.: 01-2119454392-40	reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700)  	10-25%
CAS: 16096-31-4 EINECS: 240-260-4 Reg.nr.: 01-2119463471-41	1,6-hexanediol diglycidyl ether  	10-25%
CAS: 14807-96-6 EINECS: 238-877-9	Talc (Mg3H2(SiO3)4) 	2.5-10%

Additional information:

For the wording of the listed risk phrases refer to section 16.

### 4 First-aid measures

- Description of first aid measures
- After inhalation:  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed  
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

### 5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:  
Use fire fighting measures that suit the environment.

(Contd. on page 4)

Trade name: Epifanes Epoxy Finishing Filler (comp.A)

(Contd. of page 3)

- Special hazards arising from the substance or mixture  
No further relevant information available.
- Advice for firefighters
- Protective equipment: No special measures required.

**6 Accidental release measures**

- Personal precautions, protective equipment and emergency procedures  
Not required.
- Environmental precautions:  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**7 Handling and storage**

- Handling:  
Precautions for safe handling  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.  
Ensure good ventilation/exhaustion at workplace
- Information about protection against explosions and fires:  
No special measures required.
- Conditions for safe storage, including any incompatibilities
- Storage:  
Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

**8 Exposure controls/personal protection**

- Additional information about design of technical systems:  
No further data; see item 7.
- Control parameters

Components with limit values that require monitoring at the workplace:

14807-96-6 Talc (Mg3H2(SiO3)4)

Inhalative	(Tgg)time weighted average 8 hours / Exposure time	0.25 mg/m <sup>3</sup> (Algemene bevolking/ General population)
------------	--	---

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace. (Contd. on page 5)

Trade name: Epifanes Epoxy Finishing Filler (comp.A)

(Contd. of page 4)

- Additional information:  
The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- Breathing equipment:  
Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material  
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

- Information on basic physical and chemical properties
- General Information
- Appearance:
 

Form:	Solid
Color:	According to product specification
- Odor: Characteristic
- Odour threshold: Not determined.
- pH-value at 20 °C (68 °F): 7
- Change in condition
 

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	> 200 °C (> 392 °F)
- Flash point: 151 °C (304 °F)

(Contd. on page 6)

Trade name: Epifanes Epoxy Finishing Filler (comp.A)

(Contd. of page 5)

· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	> 370 °C (> 698 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.684 g/cm <sup>3</sup> (14.053 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
VOC content:	VOC content:
· Other information	No further relevant information available.

## 10 Stability and reactivity

- Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided:  
No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Oral	LD50	11400 mg/kg bw (rat)
Dermal	LD50	>2000 mg/kg bw (rabbit)

(Contd. on page 7)

Trade name: Epifanes Epoxy Finishing Filler (comp.A)

(Contd. of page 6)

9003-36-5 reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700)

Oral	LD50	11400 mg/kg bw (rat)
Dermaal	LD50	> 2000 mg/kg bw (rabbit)

16096-31-4 1,6-hexanediol diglycidyl ether

Oral	LD50	2900 mg/kg bw (rat)
Dermaal	LD50	> 4900 mg/kg bw (rat)

- Primary irritant effect:
  - on the skin: Irritant to skin and mucous membranes.
  - on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:
  - The product shows the following dangers according to internally approved calculation methods for preparations: Irritant
- Carcinogenic categories

· IARC (International Agency for Research on Cancer)

14807-96-6	Talc (Mg3H2(SiO3)4)	2B
7631-86-9	silicon dioxide, chemically prepared	3

· NTP (National Toxicology Program)  
None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)  
None of the ingredients is listed.

## 12 Ecological information

· Toxicity

· Aquatic toxicity:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Oral	EC50	1.1 - 3.6 mg/l ((Daphnia magna))
Inhalative	LC50/96 h	1.5 - 7.7 mg/l ((Regenboogforel))

- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Ecotoxicological effects:
  - Remark: Toxic for fish
- Additional ecological information:
- General notes:
  - Water hazard class 2 (Self-assessment): hazardous for water
  - Do not allow product to reach ground water, water course or sewage system.
  - Danger to drinking water if even small quantities leak into the ground.
  - Also poisonous for fish and plankton in water bodies.
  - Toxic for aquatic organisms
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

(Contd. on page 8)

Trade name: Epifanes Epoxy Finishing Filler (comp.A)

(Contd. of page 7)

- Other adverse effects No further relevant information available.

### 13 Disposal considerations

- Waste treatment methods
- Recommendation:  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

### 14 Transport information

- UN-Number
- DOT, ADR, IMDG, IATA UN3082
- UN proper shipping name
- DOT CONSUMER COMMODITY, ORM-D  
Environmentally hazardous substances,  
liquid, n.o.s. (reaction product:  
bisphenol-A-(epichlorhydrin) epoxy resin  
(number average molecular weight = 700),  
reactie produkt: bisfenol-A-  
epichloorhydrine epoxyhars (gemiddeld  
molecuulgewicht <700))
- ADR 3082 Environmentally hazardous  
substances, liquid, n.o.s. (reaction  
product: bisphenol-A-(epichlorhydrin)  
epoxy resin (number average molecular  
weight = 700), reactie produkt: bisfenol-  
A-epichloorhydrine epoxyhars (gemiddeld  
molecuulgewicht <700))
- IMDG CONSUMER COMMODITY, ORM-D  
ENVIRONMENTALLY HAZARDOUS SUBSTANCE,  
LIQUID, N.O.S. (reaction product:  
bisphenol-A-(epichlorhydrin) epoxy resin  
(number average molecular weight = 700),  
reactie produkt: bisfenol-A-  
epichloorhydrine epoxyhars (gemiddeld  
molecuulgewicht <700)), MARINE POLLUTANT
- IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE,  
LIQUID, N.O.S. (reaction product:  
bisphenol-A-(epichlorhydrin) epoxy resin  
(number average molecular weight = 700),  
reactie produkt: bisfenol-A-  
epichloorhydrine epoxyhars (gemiddeld  
molecuulgewicht <700))

(Contd. on page 9)




Trade name: Epifanes Epoxy Finishing Filler (comp.A)

(Contd. of page 8)

· Transport hazard class(es)

· DOT, IMDG, IATA




· Class

9 Miscellaneous dangerous substances and articles

· Label

9

· ADR



· Class

9 (M6) Miscellaneous dangerous substances and articles

· Label

9

· Packing group

· DOT, ADR, IMDG, IATA

III

· Environmental hazards:

Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

· Marine pollutant:

Yes

· Special marking (ADR):

Symbol (fish and tree)

· Special marking (IATA):

Symbol (fish and tree)

Symbol (fish and tree)

· Special precautions for user

Warning: Miscellaneous dangerous substances and articles

· Danger code (Kemler):

90

· EMS Number:

F-A, S-F

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· DOT

· Quantity limitations

On passenger aircraft/rail: No limit  
On cargo aircraft only: No limit

· Remarks:

CERCLA/DOT RQ: 617gal./4786 lbs.  
Special marking with the symbol (fish and tree).

· ADR

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging:  
30 ml

Maximum net quantity per outer packaging:  
1000 ml

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging:  
30 ml

(Contd. on page 10)

Trade name: Epifanes Epoxy Finishing Filler (comp.A)

(Contd. of page 9)

·	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN3082, Environmentally hazardous substances, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700)), 9, III

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):	None of the ingredient is listed.
---	-----------------------------------

· Section 313 (Specific toxic chemical listings):	None of the ingredients is listed.
---	------------------------------------

· TSCA (Toxic Substances Control Act):	
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)
9003-36-5	reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700)
16096-31-4	1,6-hexanediol diglycidyl ether
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )
7631-86-9	silicon dioxide, chemically prepared

- Proposition 65

· Chemicals known to cause cancer:	None of the ingredients is listed.
------------------------------------	------------------------------------

· Chemicals known to cause reproductive toxicity for females:	None of the ingredients is listed.
---	------------------------------------

· Chemicals known to cause reproductive toxicity for males:	None of the ingredients is listed.
---	------------------------------------

· Chemicals known to cause developmental toxicity:	None of the ingredients is listed.
--	------------------------------------

- Cancerogenity categories

· EPA (Environmental Protection Agency)	None of the ingredients is listed.
---	------------------------------------

· TLV (Threshold Limit Value established by ACGIH)		
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	A4

· MAK (German Maximum Workplace Concentration)		
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	3B

· NIOSH-Ca (National Institute for Occupational Safety and Health)	None of the ingredients is listed.
--	------------------------------------

(Contd. on page 11)

Trade name: Epifanes Epoxy Finishing Filler (comp.A)

(Contd. of page 10)

- GHS label elements  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



GHS07 GHS08

- Signal word Warning
- Hazard-determining components of labeling:  
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)  
Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>)  
reactie produkt: bisfenol-A-epichloorhydrine epoxyhars (gemiddeld molecuulgewicht <700)  
1,6-hexanediol diglycidyl ether
- Hazard statements  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.
- Precautionary statements  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- National regulations:
- Water hazard class:  
Water hazard class 2 (Self-assessment): hazardous for water.
- Chemical safety assessment:  
A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Date of preparation / last revision 03/31/2015 / 2
- Abbreviations and acronyms:  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organisation  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists

(Contd. on page 12)

Trade name: Epifanes Epoxy Finishing Filler (comp.A)

(Contd. of page 11)

EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A  
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1  
Carc. 2: Carcinogenicity, Hazard Category 2  
\* Data compared to the previous version altered.