

**1 Identification**

- Product identifier
- Trade name: Epifanes Epoxy Primer (comp.B)
- Relevant identified uses of the substance or mixture and uses advised against
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC10 Roller application or brushing
- Environmental release category ERC2 Formulation of preparations
- Application of the substance / the mixture  
See our technical datasheet for application of this product.
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:  
W.Heeren & Zoon bv.  
P.O. box 166  
1430 AD Aalsmeer  
Netherlands  
tel.+31-(0)297-360366  
fax +31-(0)297-342078  
email: r&d@epifanes.nl
- Information department: environment protection department
- Emergency telephone number:  
Emergency Phone Number (24 hours) CHEMTREC (800-424-9300)  
Outside US: 703-527-3887

**2 Hazard(s) identification**

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R20/21: Harmful by inhalation and in contact with skin.



Xi; Irritant

R38-41: Irritating to skin. Risk of serious damage to eyes.

R10: Flammable.

- Information concerning particular hazards for human and environment:  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- Classification system:  
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

(Contd. on page 2)

Printing date 03/31/2015

Reviewed on 03/31/2015

Trade name: Epifanes Epoxy Primer (comp.B)

(Contd. of page 1)

- Label elements
- GHS label elements  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



GHS02 GHS05

- Signal word Danger
- Hazard-determining components of labeling:  
Polyaminoamide  
butan-1-ol
- Hazard statements  
H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.
- Precautionary statements  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Classification system:
- NFPA ratings (scale 0 - 4)



Health = 2  
Fire = 3  
Reactivity = 0

- HMIS-ratings (scale 0 - 4)



Health = 2  
Fire = 3  
Reactivity = 0

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

### 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description:  
Resin mixture  
Solvent mixture with additives

(Contd. on page 3)

Trade name: Epifanes Epoxy Primer (comp.B)

(Contd. of page 2)

Dangerous components:

	Polyaminoamide Xi R41 Flam. Liq. 3, H226 Eye Dam. 1, H318	50-100%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene Xn R20/21 Xi R38 R10 Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25-50%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol Xn R22 Xi R37/38-41 R10-67 Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	2.5-10%

Additional information:

For the wording of the listed risk phrases refer to section 16.

**4 First-aid measures**

- Description of first aid measures
- General information:  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation:  
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:  
Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed  
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

**5 Fire-fighting measures**

- Extinguishing media
- Suitable extinguishing agents:  
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture  
No further relevant information available.

(Contd. on page 4)

Trade name: Epifanes Epoxy Primer (comp.B)

(Contd. of page 3)

- Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

**6 Accidental release measures**

- Personal precautions, protective equipment and emergency procedures  
Wear protective clothing.  
Ensure adequate ventilation  
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:  
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**7 Handling and storage**

- Handling:  
Precautions for safe handling  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- Information about protection against explosions and fires:  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- Conditions for safe storage, including any incompatibilities
- Storage:  
Requirements to be met by storerooms and receptacles:  
Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

**8 Exposure controls/personal protection**

- Additional information about design of technical systems:  
No further data; see item 7.
- Control parameters
- Components with limit values that require monitoring at the workplace:  
1330-20-7 xylene

(Contd. on page 5)

Printing date 03/31/2015

Reviewed on 03/31/2015

Trade name: Epifanes Epoxy Primer (comp.B)

(Contd. of page 4)

Inhalative	(Tgg)time weighted average 15 min. / Exposure time	442 mg/m <sup>3</sup> (Algemene bevolking/ General population)
	(Tgg)time weighted average 8 hours / Exposure time	210 mg/m <sup>3</sup> (Algemene bevolking/ General population)

1330-20-7 xylene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

71-36-3 butan-1-ol

PEL	Long-term value: 300 mg/m <sup>3</sup> , 100 ppm
REL	Ceiling limit value: 150 mg/m <sup>3</sup> , 50 ppm Skin
TLV	Long-term value: 61 mg/m <sup>3</sup> , 20 ppm

• Ingredients with biological limit values:

1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

• Additional information:

The lists that were valid during the creation were used as basis.

• Exposure controls

• Personal protective equipment:

• General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

• Breathing equipment:

Suitable respiratory protective device recommended.  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Filter AX

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

Trade name: Epifanes Epoxy Primer (comp.B)

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable: PVA, fluorinated rubber

Glove thickness > 0.7mm, breakthrough time > 480 min. To EN374

Butyl rubber, glove thickness 0.7 mm, > 480 min breakthrough time / permeation to EN374.

· As protection from splashes gloves made of the following materials are suitable:

Nitrile

Glove thickness > 0.45 mm, breakthrough time > 30 min. to EN374

Material neoprene, nitrile protective gloves

for short-term use

(10 min <BTT <480 min):

(BTT = Break Through Time)

· Eye protection:



Tightly sealed goggles

**9 Physical and chemical properties**

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid

Color: According to product specification

· Odor: Characteristic

· Odour threshold: Not determined.

· pH-value at 20 °C (68 °F): 10

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 120 °C (248 °F)

· Flash point: 27 °C (81 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 340 °C (644 °F)

· Decomposition temperature: Not determined.

(Contd. on page 7)

Trade name: Epifanes Epoxy Primer (comp.B)

(Contd. of page 6)

· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.0 Vol %
· Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)
· Density at 20 °C (68 °F):	0.94 g/cm <sup>3</sup> (7.844 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	1400 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	42.0 %
VOC content:	42.0 %
	VOC content: 394.8 g/l / 3.29 lb/gl
Solids content:	56.0 % (VB% 1h150 C)
· Other information	No further relevant information available.

**10 Stability and reactivity**

- Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided:  
No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

**11 Toxicological information**

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values that are relevant for classification:

1330-20-7 xylene

Oral	LD50	4300 mg/kg bw (rat)
Dermal	LD50	2000 mg/kg bw (rabbit)

(Contd. on page 8)

Trade name: Epifanes Epoxy Primer (comp.B)

(Contd. of page 7)

71-36-3 butan-1-ol

Oral	LD50	790 mg/kg bw (rat)
Dermal	LD50	3400 mg/kg bw (rabbit)
Inhalative	LC50/4 h	8000 mg/l (rat)

- Primary irritant effect:
  - on the skin: Irritant to skin and mucous membranes.
  - on the eye: Strong irritant with the danger of severe eye injury.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
 

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful  
Irritant
- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

1330-20-7	xylene	3
-----------	--------	---

- NTP (National Toxicology Program)
 

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)
 

None of the ingredients is listed.

**12 Ecological information**

- Toxicity
- Aquatic toxicity:
 

1330-20-7 xylene

EC50	1 mg/l (daphnia magna) (48 uur/hour)
LC50	13.5-2.6 mg/l (Fish Acute Toxicity Study) (96 uur/hour)
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:

- Bioaccumulative potential

1330-20-7 xylene	
Log Kow	3 (not specified)

- Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:
 

Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.





Trade name: Epifanes Epoxy Primer (comp.B)

(Contd. of page 8)

**13 Disposal considerations**

- Waste treatment methods
- Recommendation:  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

**14 Transport information**

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1263
· UN proper shipping name	
· DOT	CONSUMER COMMODITY, ORM-D Paint related material
· ADR	1263 Paint related material
· IMDG	CONSUMER COMMODITY, ORM-D PAINT RELATED MATERIAL
· IATA	PAINT RELATED MATERIAL
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· ADR	
· Class	3 (F1) Flammable liquids
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E, E-S
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

(Contd. on page 10)

Trade name: Epifanes Epoxy Primer (comp.B)

(Contd. of page 9)

• Transport/Additional information:

• DOT

• Quantity limitations

On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

• Remarks:

CERCLA/DOT RQ: 617gal./4786 lbs.

• ADR

• Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging:  
30 ml

Maximum net quantity per outer packaging:  
1000 ml

• IMDG

• Limited quantities (LQ)

5L

• Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging:  
30 ml

Maximum net quantity per outer packaging:  
1000 ml

• UN "Model Regulation":

UN1263, Paint related material, 3

**15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture

• Sara

• Section 355 (extremely hazardous substances):

None of the ingredient is listed.

• Section 313 (Specific toxic chemical listings):

1330-20-7	xylene
-----------	--------

71-36-3	butan-1-ol
---------	------------

• TSCA (Toxic Substances Control Act):

All ingredients are listed.

• Proposition 65

• Chemicals known to cause cancer:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

• Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

• Cancerogenity categories

• EPA (Environmental Protection Agency)

1330-20-7	xylene	I
-----------	--------	---

71-36-3	butan-1-ol	D
---------	------------	---

(Contd. on page 11)

Trade name: Epifanes Epoxy Primer (comp.B)

(Contd. of page 10)

· TLV (Threshold Limit Value established by ACGIH)		
1330-20-7	xylene	A4
· MAK (German Maximum Workplace Concentration)		
None of the ingredients is listed.		
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients is listed.		

- GHS label elements  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



GHS02 GHS05

- Signal word Danger
- Hazard-determining components of labeling:  
Polyaminoamide  
butan-1-ol
- Hazard statements  
H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.
- Precautionary statements  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- National regulations:
- Technical instructions (air):

Class	Share in %
NK	25-50

- Water hazard class:  
Water hazard class 2 (Self-assessment): hazardous for water.
- Chemical safety assessment:  
A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Date of preparation / last revision 03/31/2015 / 2

(Contd. on page 12)

Trade name: Epifanes Epoxy Primer (comp.B)

(Contd. of page 11)

• **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer  
(Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

• \* Data compared to the previous version altered.