

1 Identification

- Product identifier
- Trade name: Epifanes Interimcoat (comp.A)
- Relevant identified uses of the substance or mixture and uses advised against
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC10 Roller application or brushing
- Environmental release category ERC2 Formulation of preparations
- Application of the substance / the mixture
See our technical datasheet for application of this product.
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
P.O. box 166
1430 AD Aalsmeer
Netherlands
tel.+31-(0)297-360366
fax +31-(0)297-342078
email: r&d@epifanes.nl
- Information department: environment protection department
- Emergency telephone number:
Emergency Phone Number (24 hours) CHEMTREC (800-424-9300)
Outside US: 703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R20: Harmful by inhalation.



Xi; Irritant

R36/37/38-43: Irritating to eyes, respiratory system and skin. May cause sensitisation by skin contact.



F; Highly flammable

R11: Highly flammable.

(Contd. on page 2)

Trade name: Epifanes Interimcoat (comp.A)

(Contd. of page 1)

- Information concerning particular hazards for human and environment:
Contact with skin and inhalation of aerosols/ vapours of the preparation should be avoided.
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- Classification system:
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- Label elements
- GHS label elements
The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



- Signal word Danger
- Hazard-determining components of labeling:
Quartz (SiO₂)
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)
4-methylpentan-2-one
titanium dioxide
- Hazard statements
H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H350 May cause cancer.
H335 May cause respiratory irritation.
- Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Classification system:
- NFPA ratings (scale 0 - 4)



Health = 1
Fire = 3
Reactivity = 0

(Contd. on page 3)

Trade name: Epifanes Interimcoat (comp.A)

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)

HEALTH	1
FIRE	3
REACTIVITY	0

Health = 1
Fire = 3
Reactivity = 0

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description:
Resin mixture
Solvent mixture with pigment additives

· Dangerous components:

CAS: 108-10-1 EINECS: 203-550-1 Index number: 606-004-00-4 Reg.nr.: 01-2119473980-30	4-methylpentan-2-one Xn R20 Xi R36/37 F R11 R66 Flam. Liq. 2, H225 Carc. 2, H351 Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335	10-25%
CAS: 14808-60-7 EINECS: 238-878-4 Reg.nr.: under C&L Inventory	Quartz (SiO ₂) Carc. 1A, H350	10-25%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	10-25%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene Xn R20/21 Xi R38 R10 Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	10-25%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) Xi R36/38-43 N R51/53 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-25%
CAS: 7727-43-7 EINECS: 231-784-4 Reg.nr.: 01-2119491274-35	barium sulphate, natural	2.5-10%
CAS: 14807-96-6 EINECS: 238-877-9	Talc (Mg ₃ H ₂ (SiO ₃) ₄) Carc. 2, H351	≤ 2.5%
CAS: 546-93-0 EINECS: 208-915-9 Reg.nr.: 01-2119523999-20	Magnesite	≤ 2.5%

(Contd. on page 4)

Trade name: Epifanes Interimcoat (comp.A)

(Contd. of page 3)

- Additional information:
For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- Description of first aid measures
- General information:
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture
No further relevant information available.
- Advice for firefighters
- Protective equipment:
Wear fully protective suit.
Mouth respiratory protective device.

*** 6 Accidental release measures**

- Personal precautions, protective equipment and emergency procedures
Ensure adequate ventilation
Wear protective clothing.
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 5)

Trade name: Epifanes Interimcoat (comp.A)

(Contd. of page 4)

See Section 13 for disposal information.

7 Handling and storage

- Handling:
 - Precautions for safe handling
Work only in fume cabinet.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about protection against explosions and fires:
 - Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- Conditions for safe storage, including any incompatibilities
- Storage:
 - Requirements to be met by storerooms and receptacles:
Store only in the original receptacle.
Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
 - Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems:
No further data; see item 7.
- Control parameters

Components with limit values that require monitoring at the workplace:

108-10-1 4-methylpentan-2-one

Inhalative	(Tgg)time weighted average 15 min. / Exposure time	208 mg/m ³ (Algemene bevolking/ General population)
	(Tgg)time weighted average 8 hours / Exposure time	104 mg/m ³ (Algemene bevolking/ General population)

14808-60-7 Quartz (SiO₂)

Inhalative	(Tgg)time weighted average 8 hours / Exposure time	0.075 mg/m ³ (general population)
------------	--	---

1330-20-7 xylene

(Contd. on page 6)

Trade name: Epifanes Interimcoat (comp.A)

(Contd. of page 5)

Inhalative	(Tgg)time weighted average 15 min. / Exposure time	442 mg/m ³ (Algemene bevolking/ General population)
	(Tgg)time weighted average 8 hours / Exposure time	210 mg/m ³ (Algemene bevolking/ General population)
14807-96-6 Talc (Mg3H2(SiO3)4)		
Inhalative	(Tgg)time weighted average 8 hours / Exposure time	0.25 mg/m ³ (Algemene bevolking/ General population)
546-93-0 Magnesite		
Inhalative	(Tgg)time weighted average 8 hours / Exposure time	10 mg/m ³ (general population)
108-10-1 4-methylpentan-2-one		
PEL	Long-term value: 410 mg/m ³ , 100 ppm	
REL	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm	
TLV	Short-term value: 307 mg/m ³ , 75 ppm Long-term value: 82 mg/m ³ , 20 ppm BEI	
14808-60-7 Quartz (SiO2)		
PEL	see Quartz listing	
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A	
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction	
1330-20-7 xylene		
PEL	Long-term value: 435 mg/m ³ , 100 ppm	
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm	
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI	
7727-43-7 barium sulphate, natural		
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction	
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction	
TLV	Long-term value: 5* mg/m ³ *inhalable fraction; E	
546-93-0 Magnesite		
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction	

(Contd. on page 7)

Printing date 03/31/2015

Reviewed on 03/31/2015

Trade name: Epifanes Interimcoat (comp.A)

(Contd. of page 6)

REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	TLV withdrawn

· Ingredients with biological limit values:

108-10-1 4-methylpentan-2-one

BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
-----	--

1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

· Additional information:

The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Breathing equipment:

Suitable respiratory protective device recommended.

In case of brief exposure or low pollution use respiratory filter device. In

case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Filter AX

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, glove thickness 0.7 mm, > 480 min breakthrough time / permeation to EN374.

(Contd. on page 8)

Trade name: Epifanes Interimcoat (comp.A)

(Contd. of page 7)

- As protection from splashes gloves made of the following materials are suitable:
Nitrile
Glove thickness > 0.45 mm, breakthrough time > 30 min. to EN374
- Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Fluid
Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	116 °C (241 °F)
· Flash point:	21 °C (70 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	460 °C (860 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	9.0 Vol %
· Vapor pressure at 20 °C (68 °F):	8 hPa (6 mm Hg)
· Density at 20 °C (68 °F):	1.37 g/cm ³ (11.433 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/ water):	
	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	120 s (ISO 6 mm)

(Contd. on page 9)

Trade name: Epifanes Interimcoat (comp.A)

(Contd. of page 8)

- Solvent content:
 - Organic solvents: 36.7 %
 - VOC content: 36.7 %
 - VOC content: 502.5 g/l / 4.19 lb/gl
- Solids content: 62.5 %
- Other information: No further relevant information available.

10 Stability and reactivity

- Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions: No dangerous reactions known.
- Conditions to avoid: No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values that are relevant for classification:

108-10-1 4-methylpentan-2-one		
Oral	LD50	2080 mg/kg bw (rat)
Dermal	LD50	16000 mg/kg bw (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)
13463-67-7 titanium dioxide		
Oral	LD50	>20000 mg/kg bw (rat)
Dermal	LD50	>10000 mg/kg bw (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)
1330-20-7 xylene		
Oral	LD50	4300 mg/kg bw (rat)
Dermal	LD50	2000 mg/kg bw (rabbit)
25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)		
Oral	LD50	11400 mg/kg bw (rat)
Dermal	LD50	>2000 mg/kg bw (rabbit)

- Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
 - on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:
 - The product shows the following dangers according to internally approved calculation methods for preparations:
 - Harmful
 - Irritant

(Contd. on page 10)

Trade name: Epifanes Interimcoat (comp.A)

(Contd. of page 9)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

108-10-1	4-methylpentan-2-one	2B
14808-60-7	Quartz (SiO ₂)	1
13463-67-7	titanium dioxide	2B
1330-20-7	xylene	3
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	2B
7631-86-9	silicon dioxide, chemically prepared	3

· NTP (National Toxicology Program)

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

1330-20-7 xylene

EC50	1 mg/l (daphnia magna) (48 uur/hour)
LC50	13.5-2.6 mg/l (Fish Acute Toxicity Study) (96 uur/hour)

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Oral	EC50	1.1 - 3.6 mg/l ((Daphnia magna))
Inhalative	LC50/96 h	1.5 - 7.7 mg/l ((Regenboogforel))

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

· Bioaccumulative potential

1330-20-7 xylene

Log Kow	3 (not specified)
---------	-------------------

· Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)

Trade name: Epifanes Interimcoat (comp.A)

(Contd. of page 10)

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

- UN-Number
- DOT, ADR, IMDG, IATA UN1263
- UN proper shipping name
- DOT CONSUMER COMMODITY, ORM-D
Paint
- ADR 1263 Paint
- IMDG CONSUMER COMMODITY, ORM-D
PAINT
- IATA PAINT

· Transport hazard class(es)

· DOT



- Class 3 Flammable liquids
- Label 3

· ADR



- Class 3 (F1) Flammable liquids
- Label 3

· IMDG, IATA



- Class 3 Flammable liquids
- Label 3

· Packing group

· DOT, ADR, IMDG, IATA III

· Environmental hazards:

- Marine pollutant: No
- Special marking (ADR): Symbol (fish and tree)

· Special precautions for user Warning: Flammable liquids

· Danger code (Kemler): 30

· EMS Number: F-E, S-E

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 12)

Trade name: Epifanes Interimcoat (comp.A)

(Contd. of page 12)

· Proposition 65

· Chemicals known to cause cancer:

108-10-1	4-methylpentan-2-one
14808-60-7	Quartz (SiO ₂)
13463-67-7	titanium dioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-10-1	4-methylpentan-2-one
----------	----------------------

· Cancerogenity categories

· EPA (Environmental Protection Agency)

108-10-1	4-methylpentan-2-one	I
1330-20-7	xylene	I
7727-43-7	barium sulphate, natural	D, CBD (inh), NL (oral)

· TLV (Threshold Limit Value established by ACGIH)

14808-60-7	Quartz (SiO ₂)	A2
13463-67-7	titanium dioxide	A4
1330-20-7	xylene	A4
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4

· MAK (German Maximum Workplace Concentration)

14808-60-7	Quartz (SiO ₂)	1
13463-67-7	titanium dioxide	3A
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	3B

· NIOSH-Ca (National Institute for Occupational Safety and Health)

14808-60-7	Quartz (SiO ₂)
13463-67-7	titanium dioxide

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Quartz (SiO₂)
 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)
 4-methylpentan-2-one
 titanium dioxide

· Hazard statements

H225 Highly flammable liquid and vapor.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.

(Contd. on page 14)

Trade name: Epifanes Interimcoat (comp.A)

(Contd. of page 13)

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	25-50

· Water hazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

· Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 03/31/2015 / 2

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 1A: Carcinogenicity, Hazard Category 1A

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· * Data compared to the previous version altered.