

**1 Identification**

- Product identifier
- Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)
- Relevant identified uses of the substance or mixture and uses advised against
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC10 Roller application or brushing
- Environmental release category ERC2 Formulation of preparations
- Application of the substance / the mixture  
See our technical datasheet for application of this product.
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:  
W.Heeren & Zoon bv.  
P.O. box 166  
1430 AD Aalsmeer  
Netherlands  
tel.+31-(0)297-360366  
fax +31-(0)297-342078  
email: r&d@epifanes.nl
- Information department: environment protection department
- Emergency telephone number:  
Emergency Phone Number (24 hours) CHEMTREC (800-424-9300)  
Outside US: 703-527-3887

**2 Hazard(s) identification**

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R20/21: Harmful by inhalation and in contact with skin.



Xi; Irritant

R38: Irritating to skin.

R10-52/53: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- Information concerning particular hazards for human and environment:  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)

Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)

(Contd. of page 1)

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02    GHS07    GHS08

· Signal word Warning

· Hazard-determining components of labeling:

4-methylpentan-2-one  
ethylbenzene

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat  
methyl-1,2,3,6,6-pentamethyl-4-piperidylsebacat  
Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)  
propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-  
5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-  
tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

· Hazard statements

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.

· Precautionary statements

P210                    Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P260                    Do not breathe dust/fume/gas/mist/vapors/spray.  
P271                    Use only outdoors or in a well-ventilated area.  
P280                    Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310            If swallowed: Immediately call a poison center/doctor.  
P303+P361+P353    IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P501                    Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1  
Fire = 3  
Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1  
Fire = 3  
Reactivity = 0

· Other hazards

- Results of PBT and vPvB assessment
- PBT: Not applicable.

(Contd. on page 3)

Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)

(Contd. of page 2)

· vPvB: Not applicable.

**3 Composition/information on ingredients**

- Chemical characterization: Mixtures
- Description:  
Mixture of the substances listed below with nonhazardous additions.














· Dangerous components:

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene Xn R20/21 Xi R38 R10 Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Xi R36 R10 Flam. Liq. 3, H226	10-25%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone Xi R36 F R11 R66-67 Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336	2.5-10%
CAS: 108-10-1 EINECS: 203-550-1 Index number: 606-004-00-4 Reg.nr.: 01-2119473980-30	4-methylpentan-2-one Xn R20 Xi R36/37 F R11 R66 Flam. Liq. 2, H225 Carc. 2, H351 Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335	2.5-10%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene Xn R20 F R11 Flam. Liq. 2, H225 Carc. 2, H351 Acute Tox. 4, H332	2.5-10%

(Contd. on page 4)

Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)

(Contd. of page 3)

<p>ELINCS: 400-830-7 Index number: 607-176-00-3 Reg.nr.: 01-2119396032-43</p>	<p>Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)</p> <p> Xi R43  N R51/53  Skin Sens. 1, H317</p>	<p>≤0.5%</p>
<p>CAS: 41556-26-7 EINECS: 255-437-1 Reg.nr.: 01-2119491304-40</p>	<p>bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacaat</p> <p> Xi R43  N R50/53  Skin Sens. 1, H317</p>	<p>≤0.5%</p>
<p>CAS: 82919-37-7 EINECS: 280-060-7 Reg.nr.: niet van toepassing</p>	<p>methyl-1,2,3,6,6-pentamethyl-4-piperidylsebacaat</p> <p> Xi R43  N R50/53  Skin Sens. 1, H317</p>	<p>≤0.5%</p>
<p>CAS: 77-58-7 EINECS: 201-039-8 Reg.nr.: 01-2119496068-27</p>	<p>dibutyltin dilaurate</p> <p> Xn R21/22-48  Xi R36/38  N R50/53  Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2A, H319</p>	<p>≤0.5%</p>

Additional information:

For the wording of the listed risk phrases refer to section 16.

**4 First-aid measures**

- Description of first aid measures
- General information:  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation:  
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:  
Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed  
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)

(Contd. of page 4)

\* **5 Fire-fighting measures**

- Extinguishing media
- Suitable extinguishing agents:  
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture  
No further relevant information available.
- Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

\* **6 Accidental release measures**

- Personal precautions, protective equipment and emergency procedures  
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

\* **7 Handling and storage**

- Handling:
  - Precautions for safe handling  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
  - Information about protection against explosions and fires:  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- Conditions for safe storage, including any incompatibilities
- Storage:
  - Requirements to be met by storerooms and receptacles: No special requirements.
  - Information about storage in one common storage facility: Not required.
  - Further information about storage conditions: Keep receptacle tightly sealed.
  - Specific end use(s) No further relevant information available.

\* **8 Exposure controls/personal protection**

- Additional information about design of technical systems:  
No further data; see item 7.

(Contd. on page 6)

Printing date 03/31/2015

Reviewed on 03/31/2015

Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)

(Contd. of page 5)

· Control parameters

· Components with limit values that require monitoring at the workplace:

1330-20-7 xylene

Inhalative	(Tgg)time weighted average 15 min. / Exposure time	442 mg/m <sup>3</sup> (Algemene bevolking/ General population)
	(Tgg)time weighted average 8 hours / Exposure time	210 mg/m <sup>3</sup> (Algemene bevolking/ General population)

108-65-6 2-methoxy-1-methylethyl acetate

Inhalative	(Tgg)time weighted average 8 hours / Exposure time	550 mg/m <sup>3</sup> (Algemene bevolking/ General population)
------------	--	--

78-93-3 butanone

Inhalative	(Tgg)time weighted average 15 min. / Exposure time	900 mg/m <sup>3</sup> (Algemene bevolking/ General population)
	(Tgg)time weighted average 8 hours / Exposure time	590 mg/m <sup>3</sup> (Algemene bevolking/ General population)

108-10-1 4-methylpentan-2-one

Inhalative	(Tgg)time weighted average 15 min. / Exposure time	208 mg/m <sup>3</sup> (Algemene bevolking/ General population)
	(Tgg)time weighted average 8 hours / Exposure time	104 mg/m <sup>3</sup> (Algemene bevolking/ General population)

100-41-4 ethylbenzene

Inhalative	(Tgg)time weighted average 15 min. / Exposure time	430 mg/m <sup>3</sup> (Algemene bevolking/ General population)
	(Tgg)time weighted average 8 hours / Exposure time	215 mg/m <sup>3</sup> (Algemene bevolking/ General population)

(Contd. on page 7)

Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)

(Contd. of page 6)

<b>1330-20-7 xylene</b>	
PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
WEEL	Long-term value: 50 ppm
<b>78-93-3 butanone</b>	
PEL	Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm BEI
<b>108-10-1 4-methylpentan-2-one</b>	
PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: 307 mg/m <sup>3</sup> , 75 ppm Long-term value: 82 mg/m <sup>3</sup> , 20 ppm BEI
<b>100-41-4 ethylbenzene</b>	
PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI

Ingredients with biological limit values:

<b>1330-20-7 xylene</b>	
BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
<b>78-93-3 butanone</b>	
BEI	2 mg/L Medium: urine Time: end of shift Parameter: MEK
<b>108-10-1 4-methylpentan-2-one</b>	
BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK

(Contd. on page 8)

Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)

(Contd. of page 7)

100-41-4 ethylbenzene

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
	- Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

- Additional information:  
The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.
- Breathing equipment:  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.  
Filter AX
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable:  
PVA, fluorinated rubber  
Glove thickness > 0.7mm, breakthrough time > 480 min. To EN374
- As protection from splashes gloves made of the following materials are suitable:  
Nitrile  
Glove thickness > 0.45 mm, breakthrough time > 30 min. to EN374

(Contd. on page 9)



Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)

(Contd. of page 8)

· Eye protection:



Tightly sealed goggles

**9 Physical and chemical properties**

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Fluid
Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	139 °C (282 °F)
· Flash point:	28 °C (82 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	315 °C (599 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	10.8 Vol %
· Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)
· Density at 20 °C (68 °F):	1.03087 g/cm <sup>3</sup> (8.603 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	43.6 %
VOC content:	43.6 %
	VOC content:
	449.6 g/l / 3.75 lb/gl

(Contd. on page 10)

Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)

(Contd. of page 9)

Solids content: 58.5 %  
 · Other information: No further relevant information available.

**10 Stability and reactivity**

- Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided:  
No decomposition if used according to specifications.
- Possibility of hazardous reactions: No dangerous reactions known.
- Conditions to avoid: No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

**11 Toxicological information**

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values that are relevant for classification:

1330-20-7 xylene		
Oral	LD50	4300 mg/kg bw (rat)
Dermal	LD50	2000 mg/kg bw (rabbit)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8532 mg/kg bw (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)
78-93-3 butanone		
Oral	LD50	3300 mg/kg bw (rat)
Dermal	LD50	5000 mg/kg bw (rabbit)
108-10-1 4-methylpentan-2-one		
Oral	LD50	2080 mg/kg bw (rat)
Dermal	LD50	16000 mg/kg bw (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)
100-41-4 ethylbenzene		
Oral	LD50	3500 mg/kg bw (rat)
Dermal	LD50	17800 mg/kg bw (rabbit)
77-58-7 dibutyltin dilaurate		
Oral	LD50	175 mg/kg bw (rat)

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant

(Contd. on page 11)

Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)

(Contd. of page 10)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7	xylene	3
108-10-1	4-methylpentan-2-one	2B
100-41-4	ethylbenzene	2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

**12 Ecological information**

· Toxicity

· Aquatic toxicity:

1330-20-7 xylene

EC50 1 mg/l (daphnia magna) (48 uur/hour)

LC50 13.5-2.6 mg/l (Fish Acute Toxicity Study) (96 uur/hour)

108-65-6 2-methoxy-1-methylethyl acetate

EC50 408-500 mg/l (daphnia magna) (48 uur/hour)

IC 50 >1000 mg/l (Algae, Growth inhibition test) (72 uur/hour)

LC50 100-180 mg/l (Fish Acute Toxicity Study) (96 uur/hour)

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

· Bioaccumulative potential

1330-20-7 xylene

Log Kow 3 (not specified)

· Mobility in soil No further relevant information available.

· Ecotoxicological effects:

· Remark: Harmful to fish

· Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

**13 Disposal considerations**

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 12)

Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)

(Contd. of page 11)

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

**14 Transport information**

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1263
· UN proper shipping name	
· DOT	CONSUMER COMMODITY, ORM-D
	Paint
· ADR	1263 Paint
· IMDG	CONSUMER COMMODITY, ORM-D
	PAINT
· IATA	PAINT
· Transport hazard class(es)	
· DOT	
· Class	3 Flammable liquids
· Label	3
· ADR, IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E, S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· Remarks:	CERCLA/DOT RQ: 617gal./4786 lbs.
· ADR	

(Contd. on page 13)

Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)

(Contd. of page 12)

· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN1263, Paint, 3, III

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7	xylene
78-93-3	butanone
108-10-1	4-methylpentan-2-one
100-41-4	ethylbenzene

· TSCA (Toxic Substances Control Act):

1330-20-7	xylene
108-65-6	2-methoxy-1-methylethyl acetate
78-93-3	butanone
108-10-1	4-methylpentan-2-one
100-41-4	ethylbenzene
25086-48-0	Azijnzure ethenylester, polymeer met chlooretheen en ethenol. Acetic acid ethenylester, polymer with chlorethene and ethanol.
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacaat
108-83-8	2,6-dimethylheptan-4-one
82919-37-7	methyl-1,2,3,6,6-pentamethyl-4-piperidylsebacaat
77-58-7	dibutyltin dilaurate
13323-62-1	Dibutylbis(octadec-9(Z)-encyloxy)stannan
5847-55-2	Dibutyltin distearate

· Proposition 65

· Chemicals known to cause cancer:

108-10-1	4-methylpentan-2-one
100-41-4	ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 14)

Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)

(Contd. of page 13)

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-10-1 4-methylpentan-2-one

· Cancerogenity categories

· EPA (Environmental Protection Agency)

1330-20-7	xylene	I
78-93-3	butanone	I
108-10-1	4-methylpentan-2-one	I
100-41-4	ethylbenzene	D

· TLV (Threshold Limit Value established by ACGIH)

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
77-58-7	dibutyltin dilaurate	A4

· MAK (German Maximum Workplace Concentration)

100-41-4	ethylbenzene	3A
----------	--------------	----

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Warning

· Hazard-determining components of labeling:

4-methylpentan-2-one  
ethylbenzene

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacaat  
methyl-1,2,3,6,6-pentamethyl-4-piperidylsebacaat  
Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)  
propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-  
5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-  
tert-butyl-4-hydroxyphenyl)propionyl-oxypoly(oxyethylene)

· Hazard statements

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 15)

Trade name: Epifanes PP Varnish Extra with UV Filter (comp.A)

(Contd. of page 14)

P301+P310 If swallowed: Immediately call a poison center/doctor.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- National regulations:
- Technical instructions (air):

Class	Share in %
NK	25-50

- Water hazard class:  
Water hazard class 2 (Self-assessment): hazardous for water.
- Chemical safety assessment:  
A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Date of preparation / last revision 03/31/2015 / 3
- Abbreviations and acronyms:  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
Flam. Liq. 2: Flammable liquids, Hazard Category 2  
Flam. Liq. 3: Flammable liquids, Hazard Category 3  
Acute Tox. 4: Acute toxicity, Hazard Category 4  
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A  
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1  
Carc. 2: Carcinogenicity, Hazard Category 2  
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
- \* Data compared to the previous version altered.